

KUBOTA Corporation

EXECUTIVE ORDER U-R-025-0407
New Off-Road

Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)							
2009	9KBXL02.6ECD	2.615	Diesel								
SPECIAL	FEATURES & EMISSION	CONTROL SYSTEMS	TYPICAL EQUIPMENT APPLICATION								
	Direct Diesel Injec	ction	Compressor, Other Industrial Equipment								

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kW-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED	EMISSION			E	EXHAUST (g/kW-l	OPACITY (%)					
POWER CLASS	STANDARD CATEGORY		HC	NOx	NMHC+NOx	СО	PM	ACCEL	LUG	PEAK	
19 ≤ kW < 37	Tier 4 Interim	STD	N/A	N/A	7.5	5.5	0.30	20	15	50	
F		CERT		(22)	5.4	1.7	0.25	1	1	2	

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Raphael Susnerry

Executed at El Monte, California on this ______ day of December 2008.

Annette Hebert, Chief

Mobile Source Operations Division

Engine Model Summary Form

KUBOTA Corporation Manufacturer:

Nonroad CI Engine category:

9KBXL02.6ECD EPA Engine Family:

Mfr Family Name: N/A

New Submission Process Code:

Attachment

U-R-025-0407

	4																				þ
8.Fuel Rate: 9.Emission Control (lbs/hr)@peak torque Device Per SAE J1930	DDI						>														-
sion Co er SAE	EM	EM	EM	EM	EM	EM	EM														
Emiss vice Pe																					
on De																					
Rate: ak torq	0	<u>ق</u>	ق	6	_	<i>د</i> ر	0														
Fuel F	14.0	13.9	13.9	13.9	11.1	11.3	10.0														
8 H/sdl)																					
te: !peak																					
uel Ra troke@ torque	39.2	38.9	38.9	38.9	38.2	39.0	34.5														
7.Fuel Rate: .mm/stroke@peak torque																					
	00	0	00	00	00	0	00		×												
6. Torque @ RPM (SEA Gross)	126.3@1600	125.4@1600	125.4@1600	125.4@1600	125.4@1300	128.4@1300	113.4@1300	- International Property of the Inte												•	
Torque (SEA	126.3	125.4	125.4	125.4	125.4	128.4	113.4										٠			-	
5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)												(B) (B) (B) (B) (B) (B) (B) (B) (B) (B)									
5.Fuel Rate: bs/hr) @ peak HI (for diesels only)	19.2	19.2	19.1	18.7	17.7	17.7	15.5														
	and because producerous																		HU,		
4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	-																				
I Rate: @ pea sel only	31.8	31.8	32.8	34.8	35.9	35.9	31.5														
4.Fue stroke for die	3	က	က	3	c	က	က														
E																N					
RPM (sec	200	200	009	400	200	200	200														
3.BHP@RPM (SAE Gross)	48.9@2700	48.9@2700	48.9@2600	48.9@2400	47.6@2200	47.6@2200	41.8@2200)			-										
		1	48	48	47	47	1	3												1 	
del	V2607-DI-ET 36.5	ا ب	Т	L		F	V2607-DI-ET 31.2	Y		,											
ne Mc	7-DI-E	V2607-DI-ET	V2607-DI-ET	V2607-DI-ET	V2607-DI-ET	V2607-DI-ET	7-DI-E														
2.Engine Model	V26C	V260	V26C	V260	V260	V260	V26[
					00000000000000000000000000000000000000																
1.Engine Code	-ET01	1-ET02	V2607-DI-ET03	-ET04	1-ET05	1-ET06	-ET07														
ngine	V2607-DI-ET01	V2607-DI-ET02	607-DI	V2607-DI-ET04	V2607-DI-ET05	V2607-DI-ET06	V2607-DI-ET07														
. Щ	2	72	72	V2	72	72	72											STATE OF THE PARTY			