

KUBOTA Corporation

EXECUTIVE ORDER U-R-025-0510 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)								
2012	CKBXL01.1DCB	1.123	Diesel 3000									
	FEATURES & EMISSION (TYPICAL EQUIPMENT APPLICATION									
·	Indirect Diesel Inje	ction	Refrigeration Unit									

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER CLASS	EMISSION			E	EXHAUST (g/kw-l	OPACITY (%)				
	STANDARD CATEGORY		HC	NOx	NMHC+NOx	co	PM:	ACCEL	LUG	PEAK
8 ≤ kW < 19	Tier 4 - Final	STD	N/A	N/A	7.5	6.6	0.40	20	15	50
		CERT	ı		6.7	1.4	0.19	6	4	10

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this

Annette Hebert, Chief

Mobile Source Operations Division

day of January 2011.

Engine Model Summary Form

category: Nonroad Cl

igine Family: CKBXL01.1DCB mily Name: N/A

ss Code: New Submission

Attachment

chment page 1 of

60# U-R-025-0510

1102/12011

	1		100		S 52 .			41.					1			 									•
8.Fuel Rate: 9.Emission Control (lbs/hr)@peak torque Device Per SAE J1930	EM INI		2.2				. :								~:										
ntr 218	F]		ŀ					١.					ľ											
유입			1.4		8.																				
io S	₽	Σ					1			ļ															
niss Pe	-	-													-								[
Ë ë								1		1										.e					
o De																:									
φ	• '																								
:: 										j]. }												
tate	_		1.					•	· .			-	1.		•										-
el F	7.3	6.2							٠.																
π.⊚	100		1.5																						
8/h	1.7	ļ			,																				
ළ							ļ.,																		
×				:																					
bea bea					47																				
Rat G	25.5	24.6													.	.									
uel Rai troke@ torque	12	5																-						i	
7.Fuel Rate: mm/stroke@peak torque			٠.						-						İ	·								i	
Ē					:						3													i	
									. ~					ľ	ļ		ľ	-							
Σ		0									7														
R (SS)	Įĕ	20											ŀ:							١.					
@ 2	8	9								Ì			'						:			7.			
due SA (52.9@1700	50.7@1500					1.3																		
6.Torque @ RPM (SEA Gross)	52	20												-											
60													.	,											
_			1						. 5.						. [
∴ુ⊨ે									6 F						. •										
eak on					3.																				
5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	9.5	8.							٠٠.				(A) (1)	ŀ						٠.					
Fue Ges	"	~			1.5			•																	
5. for											1											- A		, ,	
≝`																									
우																- :				·. '				.	
∵ <u>¥</u> ≥																	.					٠.			
pe on	_	4																						ŀ	
4.Fuel Rate: mm/stroke @ peak HP (for diesel onty)	21.7	21.4																							
T. S. S.	``	.,			1.				,				. '	ľ											
1/str (fo							٠,																		
Ē									1.																
	٠.				1									.										ı	,
¥ (ş	8	20								,			.												
R Sol	26	22	5. 15				·								.									· 	
∯ ⊕ ⊕	<u>@</u>	<u>@</u>											.					ř						.	
3.BHP@RPM (SAE Gross)	21.9@2600	19.0@2250							ļ								İ								
(7)	N	_													.									1	
े क																									
ě	Ш	Ш											:												
0	꼇	전 고	*		١.,								İ.												
2.Engine Model	D1105-ET	D1105-ET													-										
Ë		ο.									٠.				٠ ٠		İ					٠.			
2.1	1										٠.			1	İ										
	1													-		1.0									
å		ζ.			÷		'								•										
ပိ	2	è							١٠.						1										
jine Code	05-ET01	05-ET02	1														ļ				ļ			.	
<u>=</u>	<u>.</u>	12	Ι.	1	I	1	1 .	I	I.	I	1 :	I	į l	- 1	į		ı		l		I	I	1		