

KUBOTA Corporation

EXECUTIVE ORDER U-R-025-0529 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)								
2012	CKBXL01.3DCC	1.261	Diesel 3000									
	FEATURES & EMISSION C		TYPICAL EQUIPMENT APPLICATION									
	Indirect Diesel Injec	ction	Generator Set, Refrigeration	n Unit								

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED	EMISSION			E	EXHAUST (g/kw-l	OF	PACITY (%)			
POWER CLASS	STANDARD CATEGORY		HC	NOx	NMHC+NOx	co	PM	ACCEL	LUG	PEAK
8 <u><</u> kW < 19	Tier 4 Final	STD	N/A	N/A	7.5	6.6	0.40	N/A	N/A	N/A
		CERT			5.7	1.0	0.21			

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this day of December 2011

Annette Hebert, Chief

Mobile Source Operations Division

Engine Model Summary Form

Manufacturer: KUBOTA Corporation

Engine category: Nonroad Cl
EPA Engine Family: CKBXL01.3DCC

EPA Engine Family: CKB)
Mfr Family Name: N/A

Process Code: New Submission

Attachment

page 1 of 1

10 # 0-K-0x-0529

11/18/2011

	4	Le			وأعقاب ث			جي. ا						Ž2			ويتعتميني				A.M.						
8.Fuel Rate: 9.Emission Control (lbs/hr)@peak torque Device Per SAE J1930	\mathcal{H}	152 152						4.1		7	-1076	٠.			1.5				- 15/4							- '	
119 119	EM JJJ	-	500	il a			99	1 2	(10)					٠.					1							.	
Ş iji	14		75.00								100		Ť,		ZV.				, K	٠		[r				
S S	Σ	EX	M	2.7	M 1				ŽØ.	:			me.								7						
Ssić	ш	ш	ш		8				23. 7	Š.									4-3							İ	
: <u> </u>					Ž			: '											, işi								
9.E evíc										1						1										1	
۵	2			.						4.							3				igy.				3 3	-	
e <u>n</u>															9-									V.	7	-	
8 B	一個	-1.	- 735 - 143					. :		· .					12 J.	1									7	. [
<u>¥</u> 8	4	Ø	< 1									ľ															
e E	Š	N/A	N/A								8			17					7.3						#V		
_ ⊊@					3,5						37.			٠.		ļ										. \$	
s Ţs	36	* * *			6.53								đ,		40.3	-							ďe,			Ì	
€									8							M.	1.20				N.						
			V 24		rel .			**	301						112		5 P				變						
7.Fuel Rate: mm/stroke@peak torque												1:			100 PM				(40) 3.44	¥.							
e Go		-	-						7.13			1.1	10,234				4. 7			1		. !	10.2			.	
fuel Ra stroke@ torque	N/A	Ν	N/A								2007 7 Jae						9.25										
7.Fuel Rate: m/stroke@pe torque		. T		. '											MAT .									17		.	
~ <u>`</u>										3 ¹			ł "i				3.3			٠.							
E										1	() ()								. 456 5. 456		答,						
				1 2						11					70											-	
≥		٠٠.		7. j		3.73	Sec.		3.11				1										100		. No 4:3		
6. Torque @ RPM (SEA Gross)	M.						100 m						1100 1100 1100 1100 1100 1100 1100 110				15				60° 13					Mary Control	
©,Ĕ	N/A	X	Ν		かぐ						1.40		\$10				L,Ve								b ()		
A G	Z	Z	Z						N. T.		1.00									. 1		ľ	BE!				
SE													W.														
6.T (100									1 15										100						
_															kirsi. Hari			. ;	Cheir Carr				120				
à		. :									(E) (C)	ŀ						E					10 35 10 35				
5.Fuel Rate: (lbs/hr) @ peak HP · (for diesels only)																	L.									. !	
s or safe		~	變				製料		4.5														Sec.				
2 (G) 8	8.2	7.8	6.4		100		M				Solin.						勘						M.		\$ P		
E (Pie				·							\$ A				M.	ŀ	±.		2.7					1	4		
S.∱S.		10.5									33		3				3.				凝	l :		٠.			
₽)									100		1000					1 .											
		1 .	70.4. s							ľ		12		-			技業		2						2.00		
4.Fuel Rate: mm/stroke @ peak HP (for diesel only)										. :				ŀ			K.	ŀ									
:i		1_	i disa								1		DV DV	}	7		1 0.0				が変			1.			
4.Fuel Rate: stroke @ pea or diesel only	27.2	25.9	25.4						F				89		8							l					
e (e	N	N	Ñ				100		74		1,5			Ì.	à.	1						1 .					
T. P. C							X. X.		67		5.	1	6				1	1	Üz:								
, & £		1	1.5		M:						1. 95.						1		100			1					
Ē							×.74						度	l			No. of Page 2	Ì	100			ļ.	1000		35	4	
	鰋		· @				Pir.		100						6.5		1 5		Ser. Y	-		ŀ	1.7%		V.		
≨ જ	8	8	8						\$4°,				Ø.				1						100				
3.BHP@RPM (SAE Gross)	19.8@1800	19.0@1800	15.6@1500	1													1.3					į.					
90	(9)	0	(0)		\$100 g				245		14.5	1.			1.13		1000	1				F.	1				
꿆꽃	8	0	တ္					٠.									為對		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1								
6, 6)	3,	1				12.				j.,			N.				134	ļ		1.							
				2.5			13						36	1	はないというのである。	ŀ		1	150								
-			F\$.								81					4							· · · · · · · · · · · · · · · · · · ·				
de		177	1			:								. :	g :	1	13.		100		- 100		上 標		. 4		
ş	T	6	G		9.6						110		Ŋ.		Ĕ.	4	25		100	1							
ф	Φ.	m	m						-		101.6		1000		12	1	36										
:E	18	ပ္လ	S						24		M						1 300			. :		1.			1		
Ĕ	D1305-BG-ET	D1305-BG-ET	D1305-BG-ET		2 m			-					ig.				19.4		· · · · · · · · · · · · · · · · · · ·			1	1				
2.Engine Model		بب									Š.A	1		4	1000	1	100		100			1.	1	1		\vdash	_
			腦	.							100			1	Washing XX	Ŧ									Mars. Micro		
<u>o</u>	_	2	m				100			1: -				1				1	붙.					-		•	
, o	10	P	12										100			4 .				-	100	1 :	1				
S	9	9	Q.				K.				3.5										1. 1			1	M		
Ϊ	ē	80	M.	1	1	1			. :				10.00			1		1		1				1			
1.Engine Code	D1305-BG-ET01	D1305-BG-ET02	D1305-BG-ET03				157			İ	13				10	1	100	ĺ	0.4	1		1.		1			
Щ	5	2	2		. No.	1 .	1	1					87.1	1	CA.		1.						12		2480 2480		
1""		1	1 1		1000	1	1443	1	1	l	Hard .	L		1	.73	1	<u>l</u>	<u></u>	<u>1-7</u>		Leve.			L		<u>L</u>	