

## **KUBOTA Corporation**

EXECUTIVE ORDER U-R-025-0539 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFÉ (hours)							
2012	CKBXL02.0FCC	1.999	Diesel	5000							
	FEATURES & EMISSION (		TYPICAL EQUIPMENT APPLICATION								
	Indirect Diesel Inje	ction	Compressor, Generator S	Set, Welder							

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for non-methane hydrocarbon (NMHC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kW-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED	EMISSION			E	EXHAUST (g/kw-l	OPACITY (%)				
POWER CLASS	STANDARD CATEGORY		NMHC	NOx	NMHC+NOx	co	PM	ACCEL	LUG	PEAK
19 ≤ kW < 37	Interim Tier 4	STD	N/A	N/A	7.5	5.5	0.30	N/A	N/A	N/A
		CERT			5.8	0.9	0.18			

**BE IT FURTHER RESOLVED:** That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this

\_day of December 2011.

Annette Hebert, Chief

Mobile Source Operations Division

## **Engine Model Summary Form**

KUBOTA Corporation Manufacturer:

Nonroad Cl Engine category:

CKBXL02.0FCC EPA Engine Family.

**New Submission** Mfr Family Name: Process Code:

EO# U-R-0x5-0539

11/29/2011

page

	1	ekan.					جنف			Ma				Ž.			3.3			1.5						P
930	100		<b>S</b>		u.								数							n O						
ontr	100													Life.										7 91 186		
SAI	EM	EΜ	E									. 1.7			E.								100	11.4		
iissid Per		Ш	ш					1 3									9									
Ϋ́Ge.																		-								9 1 7 1 7)
တို့ ထို																-										
8.Fuel Rate: 9.Emission Control (lbs/hr)@peak torque Device Per SAE J1930																										
žė.									<u>.</u>					Ψ.												Ä,
el R. peal	N/A	Ν	X						· ·																	Ŵ.
.T.@			500									1 W 1			15.									Ů.		4
S The			11 h			1 (0) 1 (0) 1 (0)		de la companya de la																	从	
								16 ( 16 ( 13 (												gr.						#11 K
7.Fuel Rate: mm/stroke@peak torque		ë-			S VI					100					(1) (A)											
Rate Je	NA	N/A	N/A						SKA.	1 1										K K						
7.Fuel Rate: m/stroke@pe torque	Z	Z	Z							1.0		, 26.					200		West.							
7.F m/s						) Vene			農																	1
E		ad Edi									73		1						. 8							
_									Maria Maria									, .4								
6.Torque @ RPM (SEA Gross)	養傷					T.								-			Ú			Ĵ,						
@ <u>ë</u>	NA	A/N	ΑN										45.0					il.								
ÄÄ		~																								
6.To	3		98.3					145			恪							4.7		- 2X	100000 211.37		19	1		17
_																ξ										
효숙							Q.			4.54						1		14 1 + 25						1		7
5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)		~	~	ZŠ.			5.0											- 17 - 75		v. 14.1		No.		慮		
a @ e g g s	13.5	13.3	13.3		6													8		e i					14	12
F.F. Arry					NO.								1000											100		1.8
(lbs												1 (* 14) 1 (* 14)			15 All	Å.	4			8.9						ŵ,
<u></u>					in 19 Benn										8				655°	Ø,						
" ∯ ⋛				X							(1) (2) (2)						, v	74 - 1 24 - 1								
4.Fuel Rate: stroke @ pea or diesel only	33.6	33.1	33.1												\$5.1 \$5.1				\$ 1 4690			. : ::				
ke (	က်	မ်	ကိ												2,	2	Ä,				No.					
4.Fuel Rate: /stroke @ peak (for diesel only)	000										100 m	1			AT.		N.			11 .						
4.Fuel Rate: mm/stroke @ peak HP (for diesel only)					7 ¥										130				47 3 9734							
				J.	(h)					all signer.		in in														
3.BHP@RPM (SAE Gross)	33.4@1800	32.6@1800	32.6@1800				5 8															-, · · ·				
98	8	9	91						100						NA SA											
똟	4	.6(	ğ	6.35 6.35														2				7. 12 7. 12				
بر س	က်	က်					1						CAMP OF THE PARTY.						E.							
					1/2						が数										(100 to 100 to 1					
2.Engine Model	V2003-M-BG-ET	V2003-M-BG-ET	山												44				K							
Σ	BG BG	ရှိ	-BG							3	Jan.						(2.0) (1.0)									
ïe	Ş	Ž	2															34.							퉳	
E G	000	Š	g														i i									
2.5	X		18,438.1																	1						
an a			- Se																		鏖				(C)	
ŏ	ĒĪ	E10	0	1																						
ပ	86	8	8					y v		() ()						1			1000				13			
1.Engine Code	V2003-M-BG-ET01	V2003-M-BG-ET02	Į.									SARV.													No.	1
ॻ	200	200	2003							90 S.				100 PM								2				
4-	2	>	3				W.										30	1					14	14	. 1869	<u> </u>