

KUBOTA Corporation

EXECUTIVE ORDER U-R-025-0512 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)						
2012	CKBXL02.2RCD	2.216	Diesel	5000						
	FEATURES & EMISSION		TYPICAL EQUIPMENT APPLICATION							
Mechanic	al Direct Injection, Elect	ronic Control Module	Refrigeration t	Jnit						

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kW-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER	EMISSION STANDARD			E	XHAUST (g/kW-l	OPACITY (%)					
CLASS	CATEGORY		HC	NOx	NMHC+NOx	co	PM	ACCEL	LUG	PEAK	
19 <u><</u> kW < 37	Tier 4 - Interim	STD	N/A	N/A	7.5	5.5	0.30	20	15	50	
		CERT		-	6.2	1.0	0.21	2	2	2	

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this day of January 2011.

Annette Hebert, Chief

Mobile Source Operations Division

Engine Model Summary Form

acturer: KUBOTA Corporation category: Nonroad Cl

mily Name: N/A

ss Code: New Submission

Attachment

page 1 of

EO# U-R-025-0512

112/1/2011

	丛																							
	Mechanical DI			<u>-</u> .			\Rightarrow																	
Q	8					1	: 	···	· ·		1 1					·			<u> </u>			<u> </u>	Τ	*
8.Fuel Rate: 9.Emission Control (bs/hr)@peak torque_Device Per SAE J1930			onic		onic		onic																	
sion C er SAE	EM	EM	EM, Electronic	ΕM	EM, Electronic	Σ	EM, Electronic										٠.,							
Emise /ice Pe			Ξ Σ		ME		ΞŒ					٠.,												
e Dej																			• •					
te: torqu							1387							٠.										
8.Fuel Rate: 'hr)@peak to	11.3	11.8	11.8	10.0	10.0	10.0	10.0			1														
8.Fi											,								٠.					
															,		٠.							
7,Fuel Rate: mm/stroke@peak torque		က	m	_	7	_	7						_									:		
7.Fuel Rate: n/stroke@pe torque	31.7	29.3	29.3	29.7	29.7	29.7	29.7																	
7.F mm/s									<i>:</i> }											-	٠.	•		
_		_																						
6.Torque @ RPM (SEA Gross)	101.0@1600	93.7@1800	93.7@1800	93.5@1500	93.5@1500	93.5@1500	93.5@1500					. y							٠.					
rque (EA Gr	1.0@	.7@	7@	.5@	5@	.5@	50														: 1			
6.To	10	တ်	6	ဗ	6	66	ဓ																	1
₽ €									٠.						: V :									
Rate: peak l Is only	വ	ιū	2	_	_	4	4														;			
5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	12.5	14.5	14.5	12.1	12.1	11.4	11.4					14		. :										
5. (lbs/h (for																			:					
표										4.7 4.4		5 / 												:
Rate: ② peal el only	0	29.5	29.5	30.0	30.0	30.0	30.0				ì													
4.Fuel Rate: n/stroke @ peak (for diesel only)	31.0	58	28	ဗ	30	ဗ	တ္တ					igaz Z												
4.Fuel Rate: mm/stroke @ peak HP (for diesel only)												\$. *					٠.	ļ		2 1	٠.			
5 o	0	0	0	0	0	0	0				:													
@RPI Gross	9180	3220	3 220	180	180	Ø170	170																	
3.BHP@RPM (SAE Gross)	33.4@1800	37.8@2200	37.8@2200	32.1@1800	32.1@1800	30.3@1700	30.3@1700			. :										,				
		(,,	(.,																					
ode	Щ	Ψ̈	Ļ.	Ϊ́	Ļ	μ̈	ᇦ			:														
Je M	3F-DI	3L-DI	3L-DI	3-5	3L-DI	3L-D	3L-DI																	
2.Engine Model	V2203L-DI-ET	V2203L-DI-ET	V2203L-DI-ET	V2203L-DI-ET	V2203L-DI-ET	V2203L-DI-ET	V2203L-DI-ET																	
ode	ET0	=T02	:T02e	=T03	L-DI-ET03e	=T04	T04e																	
jine Code	3L-DI-ET01	3L-DI-ET02	L-DI-ET02e	3L-DI-ET03	OFE	3L-DI-ET04	L-DI-ET04e	1-						٠.										
_	1 (C)	· en	· ==	י מיז		(E)	· ***	1	•	1					' '	1		1	1	'		1		1