California	Environmental	Protection	Agency
Ø≌ Δi	r Resou	rces R	oard

KUBOTA Corporation

EXECUTIVE ORDER U-R-025-0574 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)					
2013	DKBXL01.5BCC	1.124, 1.498	Diesel	3000					
· ·	FEATURES & EMISSION		TYPICAL EQUIPMENT APPLICATION						
	Indirect Diesel Inje	ction	Generator Set, Light To	ower, Welder					

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for non-methane hydrocarbon (NMHC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED	EMISSION				EXHAUST (g/kw-l	OPACITY (%)				
POWER CLASS	STANDARD CATEGORY		NMHC NOx		NMHC+NOx	CO	PM	ACCEL	LUG	PEAK
8 ≤ kW < 19	Tier 4 Final	STD	N/A	N/A	7.5	6.6	0.40	N/A	N/A	N/A
		CERT			5.9	1.0	0.15			

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this _____ day of October 2012

Annette Hebert, Chief

Mobile Source Operations Division

Engine Model Summary Form

KUBOTA Corporation Engine category: Nonroad CI
EPA Engine Family: DKBXL01.5BCC Manufacturer:

Mfr Family Name: N/A

New Submission Process Code:

Attachment

EO# U-R-0x5-0574

Date: 9/26/2012

	1			WING.										š.									31.5	J.		k
30	IDI		>				100																			
8.Fuel Rate: 9.Emission Control (lbs/hr)@peak torque Device Per SAE J1930	H		1			4 .	1 5															1				
ŜΨ	0.000		100				36.3				4:50		J.		10 h	ļ	1	1					1		1	
ဗ ကို	Ē	ΕZ	EM																18.8			18	139			
issi Pel	۳	ш	ш						17%		in his		134							4.		4			31	
e B	B.						100		f., .									i .								٠,
6 9	1. j.).								18.					ŀ					100				14			
ம											7		1	j								Ì				
ğ										Ì	P-1						1							1		
Ę Ę	F4.								1.4		1	ļ.,			D.					-					4	
% %	7.1	10.1	9.2		10	ļ.,					C. ,:				K.		33					ļ				6
e e e	7	ĭ	တ		30		100			1	34].	6.1		1.00		100								E I	
8.Fuel Rate: hr)@peak to													2.5		14.								13%		v 18	
ps/											1434		1.78						13.7		1 2					
=									4						150		(10)			. ·	, N	İ	1.4%	1		
. K								1	100			١.	ts)									1				
je je:											10								1	١.			協震		. ,	
8 8 3	23.6	25.0	22.9				35				Š.		16.00				66				100		F			
7.Fuel Rate: mm/stroke@peak torque	N	7	V.				9.2		Dec.	-			3,540,		100		1				3.7		1:15		Ů.,	
7.F ¹√st	13									l j	S.	10	ALSAIT (學。							10	13.7%	1.		: [
Ξ.									Aller File	1 0	行						100	1							8	
		5. .5.													阿 罗										200	. [
_							膠				1.5		7					٠.								
6. Torque @ RPM (SEA Gross)	49.3@1800	70.1@1800	64.2@1800				100				1		M.							1						
(9) S	8	8	8				25					1				1				1					r d	
9 Q	(G)	0	0			100		11	143										# J		. Ç.		7,			Ì
ន្តិហ្គ	6	2.	4.2																		. 53					
5 8	4	7	Ó		1947 . 1 1944 - 1		111					1	4.5	ļ. ·	Act of							ľ.				
Ψ	40							 	1					İ	12					Ì						
•		İ					1																N o			1.7
. Ï ⊊															18 6				14.3							
g & e		_	14		21 2 2002			١.																ĺ		٠. ا
2 0 30	7	10.1	9.2				10												1			7 .				
5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)		-	٠,				l di		K.					ĺ						-					1108	·. }
28.5	200				. %				ř.					ľ		į .										
ಕ್ಕಿ			300		4		130						10.5						. [1	1			100			
۵.		1 . 1.					100														嬦		1.3		<u> </u>	ĺ
4.Fuel Rate: //stroke @ peak HP (for diesel only)															1 4				10%							•
of all te															5.14				18		0,40 1,43					ĺ
4.Fuel Rate: stroke @ pea or diesel only	23.6	25.0	22.9				50				10		MÖ						10 V 10 S	-						ļ
e (e	N	25	2				100		187	İ							ςŰ.									
7. to 12							100				3276						H.,									i
jγ.			i je				F		N			١.	40				ij,									- 1
m m	部									į							الوزر		k i					j:	Bil	. 1
	1 3		.70.3			;							9		核基									- 7		
≅ (ვ	8	8	9				主導				£ .		2													
3.BHP@RPM (SAE Gross)	16.9@1800	24.0@1800	22.0@1800		180,000								額			1 1							19 5			
9 III	0	0	(0)	1 7				1					(S)								255					
H	9	4.0	0											٠.	7) 71	10.1		. 4		- 7 - 77						
ري بي. س	Ť	2	Ŋ				4497		\$1.													1				
									P. 1					ĺ	Ž.		\$C.									
7			X 11			1	3,	,	7		\$7.0	-		ŀ		7 -		. :		9 .			176	. :		
ğ	出	EF	ᇤ		10.7						Algh,		1900 P	j		7									20 M	1.0
Ĭ	Q	Ġ	Q														S.	1								. 17
စ္	an En	-P	m				20						變	١.,	4				A ()				3			1. 7
. <u>i</u> g	Ö	20	က္ထိ		34		8.0	:	100									-27		, ,	2.5					
2.Engine Model	D1105-BG-EF	V1505-BG-EF	V1505-BG-EF				N N		37		등록비 무취						yel			~				1		
2.									影								1 2 d [3 5 d]				700					-
					4		34		2		1				A STATE OF THE STA						À	.				-
ge .	Ε,	Ξ	22												81			:			劍			1		ĺ
ĕ		H)	H				Ça				g lug								. 4		5		12.00	ļ		
. O	ਯੂ	현	o l	.			27	1	1.50		. 54 . 54	ĺ	N.							.	Æ,				M	
Ē	먑	5-B	5-8	ļ			후 구 3				- 170								115	[\$ 49			
1.Engine Code	D1105-BG-EF01	V1505-BG-EF01	V1505-8G-EF02				8		1000				Má		, 5-1-4 2 (4 - 1			:.								
<u> </u>		>	خ		54						Jakin Jaba)					į	36 T	. 4				
	احتا		133				لتعا		100			Ľ.	[83Y]					·	100	: 1	9. 1		اتيا			