Pursuant to the authority vested in California Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)		
2019	KKBXL02.4E1D	1.826, 2.435	Diesel	8000		
SPECIAL	FEATURES & EMISSION	CONTROL SYSTEMS	TYPICAL EQUIPMENT APPLICATION			
Recirculati	Direct Injection, Turboc ion, Electronic Control M Oxidizer, Diesel Oxidatio	Iodule, Periodic Trap	Loader, Tractor, Pump, Compressor, Other Industrial Equipment			

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for non-methane hydrocarbon (NMHC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER CLASS	EMISSION STANDARD CATEGORY		EXHAUST (g/kw-hr)					OPACITY (%)		
			NMHC	NOx	NMHC+NOx	со	PM	ACCEL	LUG	PEAK
19 <u>≤</u> kW < 56	Tier 4 Final	OPTIONAL STD	N/A	N/A	4.7	5.0	0.03	N/A	N/A	N/A
		CERT			3.1	0.03	0.000			

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

**BE IT FURTHER RESOLVED:** That for the listed engine models, the manufacturer has complied with the more stringent set of standards from the various power categories in conformance with Section 1039.230 (e) of the "California Exhaust Emission Standards and Test Procedures for New 2011 and Later Tier 4 Off-Road Compression Ignition Engines, Part 1-D" adopted October 20, 2005 and last amended October 25, 2012.

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this day of July 2018.

Annette Hebert, Chief Emissions Compliance, Automotive Regulations and Science Division Engine Model Summary Form

**KUBOTA** Corporation ufacturer: Nonroad CI ne category: Engine Family: KKBXL02.4E1D N/A amily Name: **New Submission** ess Code:

Attachment page 1 of 1

## EO#U-R-025-0800 Date: 7/12/2018

Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J1930
4-CR-T-EW04	C2.4-CR-T-EW	57.1@2400	42.2	22.6	144.3@1500	46.4	15.6	EM, DFI, TC, EGR, ECM, PTOX, DOC
03-CR-T-EW01	D1803-CR-T-EW	48.9@2700	43.1	19.5	109.4@1600	46.1	12.4	EM, DFI, TC, EGR, ECM, PTOX, DOC
03-CR-T-EW01	V2403-CR-T-EW	67.3@2700	44.6	26.9	152.2@1600	48.7	17.4	EM, DFI, TC, EGR, ECM, PTOX, DOC
03-CR-T-EW02	V2403-CR-T-EW	66.1@2700	44.0	26.6	144.3@1600	46.0	16.5	EM, DFI, TC, EGR, ECM, PTOX, DOC
03-CR-T-EW03	V2403-CR-T-EW	64.2@2700	43.2	26.1	144.3@1600	46.0	16.5	EM, DFI, TC, EGR, ECM, PTOX, DOC
03-CR-T-EW04	V2403-CR-T-EW	57.1@2400	42.2	22.6	144.3@1500	46.4	15.6	EM, DFI, TC, EGR, ECM, PTOX, DOC
3-CR-T-EW04L	V2403-CR-T-EW	57.1@2400	42.2	22.6	144.3@1500	46.4	15.6	EM, DFI, TC, EGR, ECM, PTOX, DOC
03-CR-T-EW05	V2403-CR-T-EW	52.3@2200	41.0	20.2	144.3@1500	46.4	15.6	EM, DFI, TC, EGR, ECM, PTOX, DOC
		· · · · · · · · · · · · · · · · · · ·						