Pursuant to the authority vested in California Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-19-095;

**IT IS ORDERED AND RESOLVED:** That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)				
2021	MKBXL02.4G3D	1.826, 2.435	Diesel	5000				
SPECIAL	FEATURES & EMISSION C	CONTROL SYSTEMS	TYPICAL EQUIPMENT APPLICATION					
Recircul	ctronic Direct Injection, ation, Electronic Contro p Oxidizer, Diesel Oxida	l Module, Periodic	Loader, Tractor, Pump, Compressor, Carrier ,Construction Machinery, Forklir Mini Backhoe, Mower, Roller, Skid Nonroad Sweeper, Welder, Wood Ch Other Industrial Equipm	ft, Garden Tractor, Steer Loader, ipper, Excavator,				

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for non-methane hydrocarbon (NMHC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED	EMISSION			ACITY (%)						
POWER CLASS	STANDARD CATEGORY		NMHC	NOx	NMHC+NOx	со	РМ	ACCEL	LUG	PEAK
19 ≤ kW < 37	Tier 4 Final	STD	N/A	N/A	4.7	5.5	0.03	N/A	N/A	N/A
		CERT			3.8	0.1	0.001			

**BE IT FURTHER RESOLVED:** That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed on this 2nd day of December 2020.

Allen Zyons, Chief Emissions Certification and Compliance Division

Model	Code	Trim	Config	Displacement	Displacement - Units	Peak Power	Peak Power - Units	Peak Power - Speed (rpm)	Peak Power - Fueling	Peak Power - Fuel Units	Peak Torque	Peak Torque - Units	Peak Torque - Speed (rpm)	Peak Torque - Fuel	Peak Torque - Fuel Units	OBD	GHG	Special	Notes
C2.4-CR-EW	C2.4-CR-EW53		I-4	2.435	Liters	33.6	kilowatt	2400	32.5	mm3/stroke	157.4	N-m	1500	38.5	mm3/stroke		N/A	N/A	N/A
C2.4-CR-EW	C2.4-CR-EW55		1-4	2.435	Liters	30.7	kilowatt	2200	32.3	mm3/stroke	157.4	N-m	1500	38.5	mm3/stroke		N/A	N/A N/A	N/A
D1803-CR-EW	D1803-CR-EW51		1-4	1.826	Liters	27.6	kilowatt	2700	32.3	mm3/stroke	114.1	N-m	1600	36.7	mm3/stroke		N/A	N/A	N/A
D1803-CR-EW	D1803-CR-EW51		1-3	1.826	Liters	27.6	kilowatt	2400	32.5	mm3/stroke	114.1	N-m	1500	36.7	mm3/stroke		N/A	N/A N/A	N/A
D1803-CR-EW	D1803-CR-EW52		1-3	1.826	Liters	22.7	kilowatt	2200	32.5	mm3/stroke	114.1	N-m	1500	36.7	mm3/stroke		N/A	N/A N/A	N/A
D1803-CR-EW	D1803-CR-EW53		1-3	2.435		30.7	kilowatt	2200	32.5	mm3/stroke	114.1	N-m	1500			-	N/A	N/A N/A	N/A
V2403-CR-EW				2.435	Liters			2200	31.8	mm3/stroke	157.4			38.5	mm3/stroke				
	V2403-CR-EW51		I-4		Liters	36	kilowatt				171	N-m	1600	40.5	mm3/stroke		N/A	N/A	N/A
V2403-CR-EW	V2403-CR-EW52	-	_	2.435	Liters	36	kilowatt	2600	31.9	mm3/stroke	-	N-m	1600	38.1	mm3/stroke		N/A	N/A	N/A
V2403-CR-EW	V2403-CR-EW53		1-4	2.435	Liters	33.6	kilowatt	2400	32.5	mm3/stroke	157.4	N-m	1500	38.5	mm3/stroke	-	N/A	N/A	N/A
V2403-CR-EW53L	V2403-CR-EW53L	-	1-4	2.435	Liters	33.6	kilowatt	2400	32.5	mm3/stroke	157.4	N-m	1500	38.5	mm3/stroke		N/A	N/A	N/A
V2403-CR-EW	V2403-CR-EW54	-	1-4	2.435	Liters	30.7	kilowatt	2200	32.2	mm3/stroke	157.4	N-m	1500	38.5	mm3/stroke	N/A	N/A	N/A	N/A
							_												
		-														_		_	
		_	_													_	_	_	_
																			_
		_									-								