

KUBOTA CORPORATION

EXECUTIVE ORDER U-R-025-1052

New Off-Road Compression-Ignition Engines Page 1 of 1

Pursuant to the authority vested in California Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)					
2023	PKBXL01.0BCB	1.002	Diesel 300						
SPECIAL	FEATURES & EMISSION C	CONTROL SYSTEMS	TYPICAL EQUIPMENT APPLICATION						
	Indirect Diesel Inje	ection	Tractor, Compressor, Generator Set, Unit, Garden Tractor, Light Tower, Mo Steer Loader, Nonroad Sweeper	ower, Roller, Skid					

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for non-methane hydrocarbon (NMHC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER CLASS	EMISSION			l	EXHAUST (g/kw-ł		OPACITY (%)			
	STANDARD CATEGORY		NMHC	NOx	NMHC+NOx	СО	PM	ACCEL	LUG	PEAK
8 ≤ kW < 19	Tier 4 Final	STD	N/A	N/A	7.5	6.6	0.40	20	15	50
		CERT			6.6	1.7	0.25	3	3	5

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed on this ______ day of October 2022.

Robin U. Lang, Chief

Emissions Certification and Compliance Division

Attachment: Engine Models EO #: U-R-025-1052 Family: PKBXL01.0BCB Attachment Last Revised: 9/24/2022

								_			_								
Model	Code	Trim	Config	Displacement	Displacement - Units	Peak Power	Peak Power - Units	Peak Power - Speed (rpm)	Peak Power - Fueling	Peak Power - Fuel Units	Peak Torque	Peak Torque - Units	Peak Torque - Speed (rpm)	Peak Torque - Fuel	Peak Torque - Fuel Units	OBD	GHG	Special	Notes
D1005-EF	D1005-EF01		1-3	1.002	Liters	18.2	kilowatt	3200	20.9	mm3/stroke	63.3	N-m	2400	22.9	mm3/stroke	N/A	N/A	N/A	N/A
D1005-EF	D1005-EF02		I-3	1.002	Liters	18.2	kilowatt	3200	20.8	mm3/stroke	61.3	N-m	2400	22.4	mm3/stroke	N/A	N/A	N/A	N/A
D1005-EF	D1005-EF02e		I-3	1.002	Liters	18.2	kilowatt	3200	20.8	mm3/stroke	61.3	N-m	2400	22.4	mm3/stroke	N/A	N/A	N/A	N/A
D1005-EF	D1005-EF03		I-3	1.002	Liters	17.2	kilowatt	3000	20.7	mm3/stroke	61.9	N-m	2200	22.6	mm3/stroke	N/A	N/A	N/A	N/A
D1005-EF	D1005-EF04		I-3	1.002	Liters	15.4	kilowatt	2800	19.7	mm3/stroke	60.9	N-m	2000	22.2	mm3/stroke	N/A	N/A	N/A	N/A
D1005-EF	D1005-EF05		I-3	1.002	Liters	14.6	kilowatt	2700	19.3	mm3/stroke	59.4	N-m	1900	21.7	mm3/stroke	N/A	N/A	N/A	N/A
D1005-EF	D1005-EF06		I-3	1.002	Liters	14.3	kilowatt	2600	19.3	mm3/stroke	60.9	N-m	1700	22.3	mm3/stroke	N/A	N/A	N/A	N/A
D1005-EF	D1005-EF07		I-3	1.002	Liters	14.0	kilowatt	2500	19.8	mm3/stroke	54.5	N-m	2000	19.8	mm3/stroke	N/A	N/A	N/A	N/A
D1005-EF	D1005-EF08		I-3	1.002	Liters	10.2	kilowatt	1800	19.8	mm3/stroke	54.4	N-m	1800	19.8	mm3/stroke	N/A	N/A	N/A	N/A
	1				1														1
	1				1														_
		_	+													_	+	+	_
																	\perp		-