

KUBOTA CORPORATION

EXECUTIVE ORDER U-L-016-0166

New Off-Road Large Spark-Ignition
Engines Above 19 Kilowatts

Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095:

IT IS ORDERED AND RESOLVED: That the following new large spark-ignition engines and emission control systems produced by the manufacturer are certified for use in off-road equipment as described below. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	FUEL TYPE		
2024	RKBXB01.5PFA	Gasoline, Liquefied Petroleum Gas (LPG), Compressed Natural Gas (CNG), Gasoline - Liquefied Petroleum Gas (LPG) Dual Fuel, Liquefied Petroleum Gas (LPG) - Compressed Natural Gas (CNG) Dual Fuel, Gasoline - Liquefied Petroleum Gas (LPG) - Compressed Natural Gas (CNG) Multi Fuel		
DURABILITY HOURS	EMISSION CONTROL SYSTEMS & SPECIAL FEATURES	EQUIPMENT APPLICATION		
5000	Three-Way Catalytic Converter (TWC), Heated Oxygen Sensors (HO2S) (2), Multiport Fuel Injection (MFI), Gaseous Fuel Mixer (MIX)	Aerial Lift, Generator, Sweeper,Tractor/Tug		

Engines certified by this Executive Order are further described in Attachment.

The following are the hydrocarbon plus oxides of nitrogen (HC+NOx) and carbon monoxide (CO) exhaust certification emission standards (Title 13, California Code of Regulations, (13 CCR) Section 2433(b)(1)) and certification emission levels for this engine family in grams per kilowatt-hour (g/kW-hr). Engines within this engine family shall have closed crankcases in conformance with 13 CCR Section 2433(b)(3).

	HC+NOx (g/kW-hr)	CO (g/kW-hr)		
EXHAUST STANDARD	0.8	20.6		
CERTIFICATION LEVEL	0.2	6.5		

The following is the evaporative hydrocarbon emission standard (13 CCR Section 2433(b)(4)) and certification emission level for this engine family in grams per gallon of fuel tank capacity (g/gallon).

EVAPORATIVE CERTIFICATION METHOD	HC CERTIFICATION LEVEL (g/gallon)	HC CERTIFICATION STANDARD (g/gallon)		
Design Based	N/A	0.2		

*not applicable

BE IT FURTHER RESOLVED: That for the listed engines for the aforementioned model-year, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2433(c) (certification and test procedures), 13 CCR Section 2434 (emission control labels), and 13 CCR Sections 2435 and 2436 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Rolin U. Lang

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed on this 8th day of November 2023.

Robin U. Lang, Chief

Emissions Certification and Compliance Division

Date: ___9/18/2023____ Engine Family: RKBXB01.5PFA For CARB Use Only
Executive Order: U-L-016-0166
Attachment __1__of__1__

Model Summary

(Use an asterisk (*) to identify worst-case engine model used for certification testing.)

S13. Engine Model		S15. Sales Codes (Check all appropriate)							
	S14. Engine Code	CA Only	49-State	50-State	S16. Engine Displacement (Liters)	S17. Rated Power (kW)	S18. Rated Speed (RPM)	S19. Peak Torque (FT-LB)	S20. Peak Torque Speed (RPM)
WG1605-G-ET	WG1605-G-ET01			X	1.537	40.48	3600	83.64	2700
WG1605-GL-ET	WG1605-GL-ET01			Х	1.537	40.48	3600	83.64	2700
WG1605-GLN-ET*	WG1605-GLN-ET01			X	1.537	40.48	3600	83.64	2700
WG1605-L-ET	WG1605-L-ET01			Х	1.537	38.05	3600	81.14	2550
WG1605-LN-ET	WG1605-LN-ET01			Х	1.537	38.05	3600	81.14	2550
WG1605-N-ET	WG1605-N-ET01			X	1.537	35.30	3600	74.28	2600