

Pursuant to the authority vested in the California Air Resources Board by Health and Safety Code Division 26, Part 5, Chapters 1 and 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: The engines and emission control systems produced by the manufacturer as described below are certified for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

Model Year	Engine Family	Combustion Cycle	Fuel Operation	Fuel Type(s)	Engine Operation
2024	RKBXL03.8C5D	Diesel	Dedicated	Diesel	Variable and Constant Speed

Emission Control Systems	Special Features
[1]: Electronic Direct Injection (DDI), Charged Air Cooler (CAC), Exhaust Gas Recirculation (EGR), Electronic Control Module (ECM), Turbocharger (TC), Diesel Oxidation Catalyst (DOC), Periodic Trap Oxidizer (PTOX), Selective Catalytic Reduction – Urea (SCR-U), Ammonia Oxidation Catalyst (AMOX)	None

The certified engine models are attached.

The listed engine models comply with the following: 1) emission standard limits (STD) and Not-To-Exceed (NTE) limits, as applicable, for criteria pollutants non-methane hydrocarbons (NMHC), nitrogen oxides (NOx), carbon monoxide (CO), and particulate matter (PM), and for smoke opacity as demonstrated during the Acceleration (ACL) and Lugging (LUG) modes, and the peak value (PEAK) in either mode of the Smoke Opacity cycle, as set forth in 13 CCR 2423 and the applicable California test procedures for off-road compression-ignition engines, and 2) family emission limits (FEL) declared by the manufacturer as allowed by the applicable California test procedures, stated in units of gram per kilowatt-hour (g/kWh-hr) and percent opacity (%opacity), respectively, except as noted, or designated as not applicable (*).

Applicable Standard		Criteria				Smoke Opacity		
		NMHC	NOx	CO	PM	ACL	LUG	PEAK
Tier 4 Final 75 ≤ kW < 130	STD	0.19	0.40	5.0	0.02	*	*	*
	FEL	*	*	*	*	*	*	*
	NTE	0.28	0.60	6.2	0.03	*	*	*

BE IT FURTHER RESOLVED: Any declared FEL is the emission limit to which all engines must comply in lieu of the standard limit for certification purposes, subject to the restrictions of averaging, banking, or trading (ABT) programs allowed by the applicable California test procedures.

BE IT FURTHER RESOLVED: That the manufacturer has elected to combine engines from the 56 ≤ kW < 130 power categories into a single engine family. The listed engine models comply with the more stringent set of standards of the 75 ≤ kW < 130 power category in accordance with Section 1039.230(e) of the applicable California test procedures.

BE IT FURTHER RESOLVED: For the listed engine models, the manufacturer has submitted materials to demonstrate certification compliance with 13 CCR 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control warranty).

BE IT FURTHER RESOLVED: The listed engine models may only be installed in or on equipment such that engine operation is consistent with off-road compression-ignition engines as defined in 13 CCR 2421(a)(39).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Executed on this 2nd day of November 2023.



Robin U. Lang, Chief
 Emissions Certification and Compliance Division

ATTACHMENT: ENGINE MODELS

Family: RKBXL03.8C5D EO Number: U-R-025-1105 Date Applicable: 10/6/2023

Model	Code	Trim	Config	Displacement	Peak Power			Peak Torque			ECS Num	GHG	Notes
					Power	Speed	Fueling	Torque	Speed	Fueling			
-	-	-	-	L	kW	rpm	mm3/stroke	N-m	rpm	mm3/stroke	-	-	-
C3.8-CR-TI-DV	C3.8-CR-TI-DV03	N/A	I4	3.77	81.8	2400	75.3	379.3	1500	84.2	1	N/A	
C3.8-CR-TI-DV	C3.8-CR-TI-DV12	N/A	I4	3.77	72.1	2400	66.8	330	1500	73.8	1	N/A	
C3.8-CR-TI-DW	C3.8-CR-TI-DW04	N/A	I4	3.77	81.8	2400	75.6	379.3	1500	84.9	1	N/A	
C3.8-CR-TI-DW	C3.8-CR-TI-DW13	N/A	I4	3.77	72.1	2400	67.1	330	1500	74.3	1	N/A	
D3.8J-CR-TI-DV	D3.8J-CR-TI-DV02	N/A	I4	3.77	85.1	2600	73.6	379.3	1500	84.2	1	N/A	
D3.8J-CR-TI-DV	D3.8J-CR-TI-DV04	N/A	I4	3.77	79.5	2200	78.8	379.3	1500	84.2	1	N/A	
D3.8J-CR-TI-DW	D3.8J-CR-TI-DW03	N/A	I4	3.77	85.1	2600	74.1	379.3	1500	84.9	1	N/A	
D3.8J-CR-TI-DW	D3.8J-CR-TI-DW05	N/A	I4	3.77	79.5	2200	79.2	379.3	1500	84.9	1	N/A	
V3800-CR-TI-DV	V3800-CR-TI-DV02	N/A	I4	3.77	85.1	2600	73.6	379.3	1500	84.2	1	N/A	
V3800-CR-TI-DV	V3800-CR-TI-DV03	N/A	I4	3.77	81.8	2400	75.3	379.3	1500	84.2	1	N/A	
V3800-CR-TI-DV	V3800-CR-TI-DV04	N/A	I4	3.77	79.5	2200	78.8	379.3	1500	84.2	1	N/A	
V3800-CR-TI-DV	V3800-CR-TI-DV05	N/A	I4	3.77	85.1	2600	74.1	379.3	1500	84.5	1	N/A	
V3800-CR-TI-DV	V3800-CR-TI-DV06	N/A	I4	3.77	77.9	2600	68	346.1	1500	77.1	1	N/A	
V3800-CR-TI-DV	V3800-CR-TI-DV07	N/A	I4	3.77	84.4	2600	73.5	363.7	1500	81	1	N/A	
V3800-CR-TI-DV	V3800-CR-TI-DV08	N/A	I4	3.77	80.7	2600	70.5	351.7	1500	78.4	1	N/A	
V3800-CR-TI-DV	V3800-CR-TI-DV09	N/A	I4	3.77	78.8	2400	73.2	362.6	1500	80.8	1	N/A	
V3800-CR-TI-DV	V3800-CR-TI-DV10	N/A	I4	3.77	70.9	2600	62.5	313.7	1500	70.8	1	N/A	
V3800-CR-TI-DV	V3800-CR-TI-DV11	N/A	I4	3.77	69	2400	64.5	330.6	1500	74.4	1	N/A	
V3800-CR-TI-DV	V3800-CR-TI-DV12	N/A	I4	3.77	72.1	2400	66.8	330	1500	73.8	1	N/A	
V3800-CR-TI-DV	V3800-CR-TI-DV13	N/A	I4	3.77	70.8	2400	65.8	347	1500	77.1	1	N/A	
V3800-CR-TI-DV	V3800-CR-TI-DV14	N/A	I4	3.77	82.2	2600	71.5	355.3	1500	79.2	1	N/A	
V3800-CR-TI-DV	V3800-CR-TI-DV15	N/A	I4	3.77	72.4	2600	63.7	319.1	1500	72	1	N/A	
V3800-CR-TI-DV	V3800-CR-TI-DV16	N/A	I4	3.77	95	2400	88.4	440	1800	97.1	1	N/A	
V3800-CR-TI-DV	V3800-CR-TI-DV17	N/A	I4	3.77	92	2200	91.8	440	1800	97.1	1	N/A	
V3800-CR-TI-DW	V3800-CR-TI-DW00	N/A	I4	3.77	97	2400	91	450	1800	100.5	1	N/A	
V3800-CR-TI-DW	V3800-CR-TI-DW03	N/A	I4	3.77	85.1	2600	74.1	379.3	1500	84.9	1	N/A	
V3800-CR-TI-DW	V3800-CR-TI-DW04	N/A	I4	3.77	81.8	2400	75.6	379.3	1500	84.9	1	N/A	
V3800-CR-TI-DW	V3800-CR-TI-DW05	N/A	I4	3.77	79.5	2200	79.2	379.3	1500	84.9	1	N/A	
V3800-CR-TI-DW	V3800-CR-TI-DW06	N/A	I4	3.77	85.1	2600	74.4	379.3	1500	85.2	1	N/A	
V3800-CR-TI-DW	V3800-CR-TI-DW07	N/A	I4	3.77	77.9	2600	68.4	346.1	1500	77.7	1	N/A	
V3800-CR-TI-DW	V3800-CR-TI-DW08	N/A	I4	3.77	84.4	2600	73.9	363.7	1500	81.7	1	N/A	
V3800-CR-TI-DW	V3800-CR-TI-DW09	N/A	I4	3.77	80.7	2600	70.9	351.7	1500	79	1	N/A	
V3800-CR-TI-DW	V3800-CR-TI-DW10	N/A	I4	3.77	78.8	2400	73.6	362.6	1500	81.5	1	N/A	
V3800-CR-TI-DW	V3800-CR-TI-DW11	N/A	I4	3.77	70.9	2600	62.8	313.7	1500	71.4	1	N/A	
V3800-CR-TI-DW	V3800-CR-TI-DW12	N/A	I4	3.77	69	2400	64.8	330.6	1500	74.9	1	N/A	
V3800-CR-TI-DW	V3800-CR-TI-DW13	N/A	I4	3.77	72.1	2400	67.1	330	1500	74.3	1	N/A	
V3800-CR-TI-DW	V3800-CR-TI-DW14	N/A	I4	3.77	70.8	2400	66.1	347	1500	77.7	1	N/A	
V3800-CR-TI-DW	V3800-CR-TI-DW15	N/A	I4	3.77	82.2	2600	71.5	355.3	1500	79.2	1	N/A	
V3800-CR-TI-DW	V3800-CR-TI-DW16	N/A	I4	3.77	72.4	2600	63.7	319.1	1500	72	1	N/A	
V3800-CR-TI-DW	V3800-CR-TI-DW17	N/A	I4	3.77	95	2400	88.7	440	1800	97.6	1	N/A	
V3800-CR-TI-DW	V3800-CR-TI-DW18	N/A	I4	3.77	92	2200	91.8	440	1800	97.6	1	N/A	
V3800-CR-TI-DW	V3800-CR-TI-DW19	N/A	I4	3.77	81.8	2400	76.1	379.3	1500	85.2	1	N/A	

ATTACHMENT: ENGINE MODELS

Family: RKBXL03.8C5D EO Number: U-R-025-1105 Date Applicable: 10/6/2023

Model	Code	Trim	Config	Displacement	Peak Power			Peak Torque			ECS Num	GHG	Notes
					Power	Speed	Fueling	Torque	Speed	Fueling			
-	-	-	-	L	kW	rpm	mm3/stroke	N-m	rpm	mm3/stroke	-	-	-
V3800-CR-TI-DW	V3800-CR-TI-DW20	N/A	I4	3.77	76.4	2400	71.5	346.1	1500	77.7	1	N/A	
V3800-CR-TI-DW	V3800-CR-TI-DW21	N/A	I4	3.77	73.9	2600	66.9	327.7	1500	74.1	1	N/A	
V3800-CR-TI-DW	V3800-CR-TI-DW22	N/A	I4	3.77	66.6	2600	61	293.5	1500	67.1	1	N/A	
V3800-CR-TI-DW	V3800-CR-TI-DW23	N/A	I4	3.77	94.2	2400	87.9	435	1800	96.5	1	N/A	
V3800-CR-TI-DW	V3800-CR-TI-DW26	N/A	I4	3.77	69.9	2600	61.9	309	1500	70.3	1	N/A	
V3800-CR-TI-DW	V3800-CR-TI-DW27	N/A	I4	3.77	64.3	2600	57.7	283	1500	64.6	1	N/A	
V3800-CR-TI-DW	V3800-CR-TI-DW30	N/A	I4	3.77	84.6	2600	74	379.3	1500	85.2	1	N/A	
V3800-CR-TI-DW	V3800-CR-TI-DW31	N/A	I4	3.77	73.5	2600	66.4	329.4	1500	74.5	1	N/A	